

P/N MS20615-5M7

Description

length: 7/16", diameter: 5/32", universal head, monel, roughly 235 pieces per pound

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS206155M7

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-725-6927

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc







^{*} See page 2 for technical characteristics

P/N MS20615-5M7 Specifications

| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
|---------------------------------------|--|
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.160 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Grip Length: | 0.194 Inches Minimum And 0.214 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20615-5M7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.