

P/N MS20615-5MP10

Military-Fasteners.com

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS206155MP10
Minimum Qty (MOQ):	50 EA
NSN:	5320-00-222-1637
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N MS20615-5MP10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/solid+rivets/MS20615-5MP10</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.