

P/N MS20615-5MP4

Description

length: 1/4", diameter: 5/32", universal head, cadmium plated monel, roughly 325 pieces per pound, MS201615 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS206155MP4

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-222-1640

Schedule B: 7508.90.0000

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



^{*} See page 2 for technical characteristics

P/N MS20615-5MP4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20615-5MP4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.