

P/N MS20615-5MP5

Military-Fasteners.com

Description

length: 5/16", diameter: 5/32", universal head, cadmium plated monel, roughly 285 pieces per pound, MS20615 series rivet

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | MS206155MP5 |
|-------------------------|--|
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-432-4608 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



P/N MS20615-5MP5 Specifications

| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
|--|---|
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.160 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/solid+rivets/MS20615-5MP5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.