

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206156CU10
Minimum Qty (MOQ):	1000 EA
NSN:	5320-00-771-7580
Schedule B:	7415.29.0000
ECCN:	9A991
National Motor Freight:	096300, Rivets Brass / Bronze / Copper

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20615-6CU10 Specifications

<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Grip Length:</b>	0.334 Inches Minimum And 0.354 Inches Maximum
<b>Shear Strength:</b>	17000 Single Pounds Per Square Inch
<b>Material:</b>	Copper Alloy Overall
<b>Material Document And Classification:</b>	Qq-w-341 Fed Spec Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-6CU10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.