

## P/N MS20615-6M10

### **Description**

length: 5/8", diameter: 3/16", universal head monel, roughly 120 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS206156M10

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-550-2401

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20615-6M10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Grip Length:	0.334 Inches Minimum And 0.354 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

# **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615-6M10">https://military-fasteners.com/rivets/solid+rivets/MS20615-6M10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.