

Description

Fastener Length: 13/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS206156M13
Minimum Qty (MOQ):	25
NSN:	5320-00-935-3723
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N MS20615-6M13 Specifications

Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Grip Length:	0.438 Nominal Mils
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy Overall
Material Document And Classification:	Qq-n-281,class A Fed Spec Single Material Response Overall
Specification/standard Data:	96906-ms20615 Government Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-6M13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.