

Description

length: 3/16", diameter: 3/16", universal head, monel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206156M3
Minimum Qty (MOQ):	50
NSN:	5320-01-453-2320
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS20615-6M3 Specifications

Fastener Length:	0.1775 Inches Minimum And 0.1975 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
End Item Identification:	F-15
Shear Strength:	49000 Single Pounds Per Square Inch
Criticality Code Justification:	Agav
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-6M3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.