

**Description**

length: 3/16", diameter: 3/16", universal head, monel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS206156M3
Minimum Qty (MOQ):	50
NSN:	5320-01-453-2320
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N MS20615-6M3 Specifications

<b>Fastener Length:</b>	0.1775 Inches Minimum And 0.1975 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>End Item Identification:</b>	F-15
<b>Shear Strength:</b>	49000 Single Pounds Per Square Inch
<b>Criticality Code Justification:</b>	Agav
<b>Material:</b>	Nickel Alloy 400 Overall
<b>Material Document And Classification:</b>	Qq-n-281 Fed Spec Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-6M3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.