

P/N MS20615-6M5

Description

length: 5/16", diameter: 3/16", universal head, monel, roughly 180 pieces per pound, MS20615 series rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS206156M5

Minimum Qty (MOQ): 1 Pound

NSN: 5320-00-584-1598

Schedule B: 7508.90.5000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc







^{*} See page 2 for technical characteristics

P/N MS20615-6M5 Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Grip Length:	0.021 Inches Minimum And 0.041 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20615-6M5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.