

Description

length: 7/16", diameter: 3/16", universal head, monel, roughly 150 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS206156M7 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-993-7107 |
| ECCN: | EAR99 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |



P/N MS20615-6M7 Specifications

| | |
|--|--|
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.191 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Grip Length: | 0.147 Inches Minimum And 0.167 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-6M7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.