

Description

Fastener Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS206158M16
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-771-7527
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N MS20615-8M16 Specifications

Fastener Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.254 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615-8M16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.