

Description

Fastener Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS20615M511 |
| Minimum Qty (MOQ): | 45 EA |
| NSN: | 5320-00-808-0814 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N MS20615M5-11 Specifications

| | |
|--|--|
| Fastener Length: | 0.678 Inches Minimum And 0.698 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.067 Inches Minimum And 0.077 Inches Maximum |
| Shank Diameter: | 0.155 Inches Minimum And 0.160 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Grip Length: | 0.444 Inches Minimum And 0.464 Inches Maximum |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Material: | Nickel Alloy 400 Overall |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615M5-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.