

# P/N MS20615M5-12

## **Description**

MS20615M5-12 Solid Rivet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

## **Additional Information**

#### **Alternate Part Numbers**

## MS20615-5M12

SKU / Model: MS20615M512

Minimum Qty (MOQ): 50

NSN: 5320-00-401-5289

ECCN: EAR99

National Motor Freight: 139820, Nickel Bolts / Nails / Nuts / Rivets Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20615M5-12 Specifications

| Fastener Length:                      | 0.740 Inches Minimum And 0.760 Inches Maximum      |
|---------------------------------------|--|
| Head Style:                           | Universal  |
| Head Height:                          | 0.067 Inches Minimum And 0.077 Inches Maximum      |
| Shank Diameter:                       | 0.155 Inches Minimum And 0.160 Inches Maximum      |
| Shank Style:                          | Straight   |
| Head Major Diameter:                  | 0.296 Inches Minimum And 0.328 Inches Maximum      |
| Shear Strength:                       | 49000 Single Pounds Per Square Inch                |
| Material:                             | Nickel Alloy 400 Overall                           |
| Material Document And Classification: | Qq-n-281 Fed Spec Single Material Response Overall |

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20615M5-12">https://military-fasteners.com/rivets/solid+rivets/MS20615M5-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.