

Description

Fastener Length: 1/4, roughly 325 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS20615-5M4](#)

SKU / Model:	MS20615M54
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-989-3171
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N MS20615M5-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Grip Length:	0.006 Inches Minimum And 0.026 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20615M5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.