

Description

cable diameter: 1/16", corrosion resistant steel, 480 lbs. minimum breaking strength, MS20663 series ball end


* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS20663-C2](#) [AN663C2](#)

SKU / Model:	MS20663C2
Minimum Qty (MOQ):	20
NSN:	4030-00-273-3080
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



* See page 2 for technical characteristics

P/N MS20663C2 Specifications

Inside Diameter:	0.073 Inches Minimum And 0.077 Inches Maximum
Head Diameter:	0.203 Inches Minimum And 0.207 Inches Maximum
Overall Length:	0.355 Inches Minimum And 0.370 Inches Maximum
Plain Shank Diameter:	0.123 Inches Minimum And 0.127 Inches Maximum
Accommodated Material Diameter:	0.062 Inches Nominal
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Style Designator:	Oval With Double Shank

How to Order

Order this wire rope swaging ball end from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20663C2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.