

## P/N MS20663C2

### **Description**

cable diameter: 1/16", corrosion resistant steel, 480 lbs. minimum breaking strength, MS20663 series ball end

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

MS20663-C2 AN663C2

SKU / Model: MS20663C2

Minimum Qty (MOQ): 20

NSN: 4030-00-273-3080

ECCN: EAR99

National Motor Freight: 105200, Fittings Cable / Chain / Rope I / S









# **P/N MS20663C2 Specifications**

Inside Diameter:	0.073 Inches Minimum And 0.077 Inches Maximum
Head Diameter:	0.203 Inches Minimum And 0.207 Inches Maximum
Overall Length:	0.355 Inches Minimum And 0.370 Inches Maximum
Plain Shank Diameter:	0.123 Inches Minimum And 0.127 Inches Maximum
Accommodated Material Diameter:	0.062 Inches Nominal
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Style Designator:	Oval With Double Shank

# **How to Order**

Order this wire rope swaging ball end from our inventory online by visiting <a href="https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20663C2">https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20663C2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.