

Description

cable diameter: 3/32", corrosion resistant steel, 900 lbs. minimum breaking strength, double shank, MS20663 series ball end

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20663C3
Minimum Qty (MOQ):	10
NSN:	4030-00-273-3073
ECCN:	9A991
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



P/N MS20663C3 Specifications

Inside Diameter:	0.104 Inches Minimum And 0.108 Inches Maximum
Head Diameter:	0.273 Inches Minimum And 0.277 Inches Maximum
Overall Length:	0.5175 Inches Minimum And 0.5325 Inches Maximum
Plain Shank Diameter:	0.159 Inches Minimum And 0.167 Inches Maximum
Accommodated Material Diameter:	0.094 Inches Nominal
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Style Designator:	Oval With Double Shank

How to Order

Order this wire rope swaging ball end from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20663C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.