

**Description**

cable diameter: 3/32", corrosion resistant steel, 900 lbs. minimum breaking strength, double shank, MS20663 series ball end

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20663C3
Minimum Qty (MOQ):	10
NSN:	4030-00-273-3073
ECCN:	9A991
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



## P/N MS20663C3 Specifications

<b>Inside Diameter:</b>	0.104 Inches Minimum And 0.108 Inches Maximum
<b>Head Diameter:</b>	0.273 Inches Minimum And 0.277 Inches Maximum
<b>Overall Length:</b>	0.5175 Inches Minimum And 0.5325 Inches Maximum
<b>Plain Shank Diameter:</b>	0.159 Inches Minimum And 0.167 Inches Maximum
<b>Accommodated Material Diameter:</b>	0.094 Inches Nominal
<b>Material:</b>	Steel Corrosion Resisting
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Oval With Double Shank

## How to Order

Order this wire rope swaging ball end from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20663C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.