

Description

cabl diameter: 1/16", corrosion resistant steel, 480 lbs. minimum strength, MS20664 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS20664-C2](#)

SKU / Model:	MS20664C2
Minimum Qty (MOQ):	25
NSN:	4030-00-273-3081
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



P/N MS20664C2 Specifications

Inside Diameter:	0.073 Inches Minimum And 0.077 Inches Maximum
Head Diameter:	0.208 Inches Minimum And 0.212 Inches Maximum
Overall Length:	0.263 Inches Minimum And 0.274 Inches Maximum
Plain Shank Diameter:	0.128 Inches Minimum And 0.132 Inches Maximum
Accommodated Material Diameter:	0.062 Inches Nominal
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Style Designator:	Oval With Single Shank

How to Order

Order this wire rope swaging ball end from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20664C2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.