

**Description**

cable diameter: 1/16", corrosion resistant steel, 480 lbs. minimum strength, MS20664 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**MS20664-C2

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20664C2                                   |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 4030-00-273-3081                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 105200, Fittings Cable / Chain / Rope I / S |



\* See page 2 for technical characteristics

# P/N MS20664C2 Specifications

|                                 |   |
|---------------------------------|---|
| Inside Diameter:                | 0.073 Inches Minimum And 0.077 Inches Maximum |
| Head Diameter:                  | 0.208 Inches Minimum And 0.212 Inches Maximum |
| Overall Length:                 | 0.263 Inches Minimum And 0.274 Inches Maximum |
| Plain Shank Diameter:           | 0.128 Inches Minimum And 0.132 Inches Maximum |
| Accommodated Material Diameter: | 0.062 Inches Nominal                          |
| Material:                       | Steel Corrosion Resisting                     |
| Surface Treatment:              | Passivate                                     |
| Style Designator:               | Oval With Single Shank                        |

## How to Order

Order this wire rope swaging ball end from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20664C2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.