

Description

cable diameter: 3/32", corrosion resistant steel, 900 lbs. minimum breaking strength, MS20664 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20664C3
Minimum Qty (MOQ):	20
NSN:	1640-00-272-7750
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



P/N MS20664C3 Specifications

Inside Diameter:	0.104 Inches Minimum And 0.108 Inches Maximum
Head Diameter:	0.278 Inches Minimum And 0.286 Inches Maximum
Overall Length:	0.379 Inches Minimum And 0.389 Inches Maximum
Plain Shank Diameter:	0.164 Nominal Mils And 0.172 Nominal Centimeters
Accommodated Material Diameter:	0.094 Inches Nominal
Special Features:	Flight Safety Critical
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Style Designator:	Oval With Single Shank

How to Order

Order this wire rope swaging ball end from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20664C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.