

**Description**

cable diameter: 3/32", corrosion resistant steel, 900 lbs. minimum breaking strength, MS20664 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20664C3
Minimum Qty (MOQ):	20
NSN:	1640-00-272-7750
ECCN:	EAR99
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S



## P/N MS20664C3 Specifications

<b>Inside Diameter:</b>	0.104 Inches Minimum And 0.108 Inches Maximum
<b>Head Diameter:</b>	0.278 Inches Minimum And 0.286 Inches Maximum
<b>Overall Length:</b>	0.379 Inches Minimum And 0.389 Inches Maximum
<b>Plain Shank Diameter:</b>	0.164 Nominal Mils And 0.172 Nominal Centimeters
<b>Accommodated Material Diameter:</b>	0.094 Inches Nominal
<b>Special Features:</b>	Flight Safety Critical
<b>Material:</b>	Steel Corrosion Resisting
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Oval With Single Shank

## How to Order

Order this wire rope swaging ball end from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20664C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.