

Description

3/16" cable diameter - corrosion resistant steel - 4,200 lbs. minimum breaking strength

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20664C6
Minimum Qty (MOQ):	1
NSN:	4030-00-272-7749
National Motor Freight:	105200, Fittings Cable / Chain / Rope I / S

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20664C6 Specifications

Inside Diameter:	0.201 Inches Minimum And 0.205 Inches Maximum
Head Diameter:	0.487 Inches Minimum And 0.492 Inches Maximum
Overall Length:	0.725 Inches Minimum And 0.735 Inches Maximum
Plain Shank Diameter:	0.293 Inches Minimum And 0.298 Inches Maximum
Accommodated Material Diameter:	0.188 Inches Nominal
Material:	Steel Comp 305 Or Steel Comp 303se
Material Document And Classification:	66 Fed Std All Material Responses
Surface Treatment:	Passivate
Style Designator:	Oval With Single Shank

How to Order

Order this wire rope swaging ball end from our inventory online by visiting <https://military-fasteners.com/fittings/wire+rope+swaging+ball+ends/MS20664C6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.