



★ FASTENERS

Military-Fasteners.com

P/N MS20668-4

Description

cable diameter: 1/8", corrosion resistant steel, 2,000 lbs. minimum breaking strength

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|----------------------------|
| SKU / Model: | MS206684 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 4030-00-132-9181 |
| ECCN: | EAR99 |
| National Motor Freight: | 011790, Aircraft Parts Noi |



* See page 2 for technical characteristics

P/N MS20668-4 Specifications

| | |
|---|--|
| Inside Diameter: | 0.154 Inches Nominal |
| Overall Width: | 0.500 Inches Nominal |
| Plain Shank Diameter: | 0.219 Inches Nominal |
| End Item Identification: | Mrap |
| Length From Pinhole Center To End: | 2.337 Inches Nominal |
| Accommodated Material Diameter: | 0.125 Inches Nominal |
| Bolt Hole Diameter: | 0.190 Inches Nominal |
| Breaking Strength: | 2000.0 Pounds Nominal |
| Overall Height: | 0.500 Inches Nominal |
| Material: | Steel |
| Surface Treatment: | Passivate |
| Surface Treatment Document And Classification: | Mil-dtl-781 Mil Spec Single Treatment Response |
| Style Designator: | Ball End |

How to Order

Order this rope swaging terminal from our inventory online by visiting <https://military-fasteners.com/fittings/rope+swaging+terminals/MS20668-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.