

**Description**

outer diameter: 3/4", flared tube fitting, corrosion resistant, MS20819 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AS5176J12](#)

SKU / Model:	MS2081912J
Minimum Qty (MOQ):	5
NSN:	4730-00-204-3454
Schedule B:	7307.22.1000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



\* See page 2 for technical characteristics

## P/N MS20819-12J Specifications

<b>Casehardening Indicator:</b>	Not Casehardened
<b>Overall Length:</b>	0.688 Inches Nominal
<b>Flange Width:</b>	0.266 Inches Nominal
<b>Flange Outside Diameter:</b>	0.972 Inches Nominal
<b>Seat Angle In Deg:</b>	33.0
<b>Sleeve Outside Diameter:</b>	0.826 Inches Nominal
<b>Hose/tube Outside Diameter For Which Designed:</b>	0.750 Inches Nominal
<b>Material:</b>	Steel, Qq-s-763, Class 304
<b>Material:</b>	Steel Comp 304
<b>Surface Treatment:</b>	Passivated,qq-p-35,type 1
<b>Style Designator:</b>	Sleeve
<b>Surface Treatment:</b>	Passivated,qq-p-35,type 1

## How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-12J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.