

Description

Outer diameter: 1", flared, aluminum alloy, anodize blue, MS20819 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2081916D
Minimum Qty (MOQ):	5
NSN:	4730-01-079-2858
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



P/N MS20819-16D Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.765 Inches Minimum And 0.797 Inches Maximum
Flange Width:	0.265 Inches Minimum And 0.297 Inches Maximum
Flange Outside Diameter:	1.219 Inches Minimum And 1.222 Inches Maximum
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	1.078 Inches Minimum And 1.081 Inches Maximum
Hose/tube Outside Diameter For Which Designed:	1.000 Inches Nominal
Material:	Aluminum Alloy, Qq-a-225/4
Material:	Aluminum Alloy 2014
Surface Treatment:	Anodize
Style Designator:	Sleeve
Surface Treatment:	Anodized, Mil-a-8625, Type 2

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-16D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.