

Description

Outer diameter: 1", flared, aluminum alloy, anodize blue, MS20819 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------|
| SKU / Model: | MS2081916D |
| Minimum Qty (MOQ): | 5 |
| NSN: | 4730-01-079-2858 |
| Schedule B: | 7609.00.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



P/N MS20819-16D Specifications

| | |
|---|---|
| Casehardening Indicator: | Not Casehardened |
| Overall Length: | 0.765 Inches Minimum And 0.797 Inches Maximum |
| Flange Width: | 0.265 Inches Minimum And 0.297 Inches Maximum |
| Flange Outside Diameter: | 1.219 Inches Minimum And 1.222 Inches Maximum |
| Seat Angle In Deg: | 33.0 |
| Sleeve Outside Diameter: | 1.078 Inches Minimum And 1.081 Inches Maximum |
| Hose/tube Outside Diameter For Which Designed: | 1.000 Inches Nominal |
| Material: | Aluminum Alloy, Qq-a-225/4 |
| Material: | Aluminum Alloy 2014 |
| Surface Treatment: | Anodize |
| Style Designator: | Sleeve |
| Surface Treatment: | Anodized, Mil-a-8625, Type 2 |

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-16D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.