

**Description**

Outer diameter: 1", flared, aluminum alloy, anodize blue, MS20819 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2081916D
Minimum Qty (MOQ):	5
NSN:	4730-01-079-2858
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



## P/N MS20819-16D Specifications

<b>Casehardening Indicator:</b>	Not Casehardened
<b>Overall Length:</b>	0.765 Inches Minimum And 0.797 Inches Maximum
<b>Flange Width:</b>	0.265 Inches Minimum And 0.297 Inches Maximum
<b>Flange Outside Diameter:</b>	1.219 Inches Minimum And 1.222 Inches Maximum
<b>Seat Angle In Deg:</b>	33.0
<b>Sleeve Outside Diameter:</b>	1.078 Inches Minimum And 1.081 Inches Maximum
<b>Hose/tube Outside Diameter For Which Designed:</b>	1.000 Inches Nominal
<b>Material:</b>	Aluminum Alloy, Qq-a-225/4
<b>Material:</b>	Aluminum Alloy 2014
<b>Surface Treatment:</b>	Anodize
<b>Style Designator:</b>	Sleeve
<b>Surface Treatment:</b>	Anodized, Mil-a-8625, Type 2

## How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-16D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.