

Description

MS20819-20D Flared Tube Fitting Sleeve

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2081920D
Minimum Qty (MOQ):	5
NSN:	4730-01-118-1307
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



NO IMAGE
AVAILABLE

P/N MS20819-20D Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.890 Inches Minimum And 0.922 Inches Maximum
End Item Identification:	Aircraft Grumman Model NO.a10
Flange Width:	0.296 Inches Minimum And 0.328 Inches Maximum
Flange Outside Diameter:	1.531 Inches Minimum And 1.534 Inches Maximum
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	1.336 Inches Minimum And 1.339 Inches Maximum
Hose/tube Outside Diameter For Which Designed:	1.250 Inches Nominal
Material:	Aluminum Alloy, Qq-a-225/4, Alloy 2014, T6 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024, T6 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024, T851
Material:	Aluminum Alloy 2014 Or Aluminum Alloy 2024 Or Aluminum Alloy 2024
Surface Treatment:	Anodize
Style Designator:	Sleeve
Surface Treatment:	Anodized, Mil-a-8625, Type 2, Class 2

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-20D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.