

Description

tube outer dia: 1/8", flared tube fitting - aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208192D
Minimum Qty (MOQ):	10
NSN:	4730-01-070-6528
National Motor Freight:	051400, Pipe Fittings Aluminum

NO IMAGE
AVAILABLE

P/N MS20819-2D Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.328 Inches Minimum And 0.360 Inches Maximum
Flange Width:	0.109 Inches Minimum And 0.141 Inches Maximum
Flange Outside Diameter:	0.264 Inches Minimum And 0.267 Inches Maximum
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	0.169 Inches Minimum And 0.172 Inches Maximum
Hose/tube Outside Diameter For Which Designed:	0.125 Inches Nominal
Material:	Aluminum Alloy, Qq-a-225/4 Or Aluminum Alloy, Qq-a-225/6, Alloy 2024
Material:	Aluminum Alloy 2014 Or Aluminum Alloy 2024
Surface Treatment:	Anodize
Style Designator:	Sleeve
Surface Treatment:	Anodized, Mil-a-8625, Type 2

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-2D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.