

## P/N MS20819-3D

### **Description**

outer diameter: 3/16", flared tube, aluminum alloy, MS20819 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS208193D

Minimum Qty (MOQ): 20

NSN: 4730-01-163-6996

ECCN: 9A991.d

National Motor Freight: 051400, Pipe Fittings Aluminum









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20819-3D Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.390 Inches Minimum And 0.422 Inches Maximum
Flange Width:	0.125 Inches Minimum And 0.157 Inches Maximum
Flange Outside Diameter:	0.329 Inches Minimum And 0.332 Inches Maximum
Seat Angle In Deg:	32.0
Sleeve Outside Diameter:	0.234 Inches Minimum And 0.237 Inches Maximum
Hose/tube Outside Diameter For Which Designed:	0.188 Inches Nominal
Material:	Aluminum Alloy, Qq-a-225/4, Alloy 2014, T6
Material:	Aluminum Alloy, Qq-a-367, Alloy 7075, T73
Surface Treatment:	Anodize
Style Designator:	Sleeve
Surface Treatment:	Anodized, Mil-a-8625, Type 2
Specification/standard Data:	96906-ms20819-3d Government Standard

## **How to Order**

Order this flared tube fitting sleeve from our inventory online by visiting <a href="https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-3D">https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-3D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.