

Description

outer diameter: 3/16", flared tube, corrosion resistant, MS20819 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208193J
Minimum Qty (MOQ):	10
NSN:	4730-00-540-0454
Schedule B:	7307.22.1000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS20819-3J Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.406 Inches Nominal
Metallic Hardness Rating:	10.0 Minimum Rockwell C And 31.0 Maximum Rockwell C
Flange Width:	0.141 Inches Nominal
Flange Outside Diameter:	0.329 Inches Nominal
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	0.234 Inches Nominal
Hose/tube Outside Diameter For Which Designed:	0.188 Inches Nominal
Material:	Steel, Fed Std 66, Comp 304
Material:	Steel Comp 304
Surface Treatment:	Passivate
Style Designator:	Sleeve
Surface Treatment:	Passivated

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-3J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.