

**Description**

outer diameter: 3/16", flared tube, corrosion resistant, MS20819 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AS5176J03](#)

SKU / Model:	MS208193J
Minimum Qty (MOQ):	5
NSN:	4730-00-540-0454
Schedule B:	7307.22.1000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



\* See page 2 for technical characteristics

## P/N MS20819-3J Specifications

<b>Casehardening Indicator:</b>	Not Casehardened
<b>Overall Length:</b>	0.406 Inches Nominal
<b>Metallic Hardness Rating:</b>	10.0 Minimum Rockwell C And 31.0 Maximum Rockwell C
<b>Flange Width:</b>	0.141 Inches Nominal
<b>Flange Outside Diameter:</b>	0.329 Inches Nominal
<b>Seat Angle In Deg:</b>	33.0
<b>Sleeve Outside Diameter:</b>	0.234 Inches Nominal
<b>Hose/tube Outside Diameter For Which Designed:</b>	0.188 Inches Nominal
<b>Material:</b>	Steel, Fed Std 66, Comp 304
<b>Material:</b>	Steel Comp 304
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Sleeve
<b>Surface Treatment:</b>	Passivated

## How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-3J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.