

**Description**

outer diameter: 1/4", flared tube fitting, aluminum alloy, MS20819 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS208194D
Minimum Qty (MOQ):	20
NSN:	4730-00-302-8641
Schedule B:	7609.00.0000
ECCN:	EAR99



## P/N MS20819-4D Specifications

<b>Casehardening Indicator:</b>	Not Casehardened
<b>Overall Length:</b>	0.390 Inches Minimum And 0.422 Inches Maximum
<b>Flange Width:</b>	0.125 Inches Minimum And 0.157 Inches Maximum
<b>Flange Outside Diameter:</b>	0.380 Inches Minimum And 0.383 Inches Maximum
<b>Seat Angle In Deg:</b>	33.0
<b>Sleeve Outside Diameter:</b>	0.294 Inches Minimum And 0.297 Inches Maximum
<b>Hose/tube Outside Diameter For Which Designed:</b>	0.250 Inches Nominal
<b>Material:</b>	Aluminum Alloy
<b>Material:</b>	Aluminum Alloy
<b>Surface Treatment:</b>	Anodize
<b>Style Designator:</b>	Sleeve
<b>Surface Treatment:</b>	Anodized, Mil-a-8625, Type 2

## How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.