

Description

outer diameter: 1/4", flared tube fitting, aluminum alloy, MS20819 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208194D
Minimum Qty (MOQ):	20
NSN:	4730-00-302-8641
Schedule B:	7609.00.0000
ECCN:	EAR99



P/N MS20819-4D Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.390 Inches Minimum And 0.422 Inches Maximum
Flange Width:	0.125 Inches Minimum And 0.157 Inches Maximum
Flange Outside Diameter:	0.380 Inches Minimum And 0.383 Inches Maximum
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	0.294 Inches Minimum And 0.297 Inches Maximum
Hose/tube Outside Diameter For Which Designed:	0.250 Inches Nominal
Material:	Aluminum Alloy
Material:	Aluminum Alloy
Surface Treatment:	Anodize
Style Designator:	Sleeve
Surface Treatment:	Anodized, Mil-a-8625, Type 2

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.