

**Description**

Length: 13/32", stainless steel, passivate surface, MS20819 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS208194K
Minimum Qty (MOQ):	5
NSN:	4730-00-629-0868
Schedule B:	7307.22.1000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



\* See page 2 for technical characteristics

## P/N MS20819-4K Specifications

<b>Casehardening Indicator:</b>	Casehardened
<b>Overall Length:</b>	0.410 Inches Nominal
<b>Metallic Hardness Rating:</b>	70.0 Minimum Rockwell B And 95.0 Maximum Rockwell B
<b>Flange Width:</b>	0.140 Inches Nominal
<b>Flange Outside Diameter:</b>	0.383 Inches Nominal
<b>Seat Angle In Deg:</b>	33.0
<b>Sleeve Outside Diameter:</b>	0.328 Inches Nominal
<b>Hose/tube Outside Diameter For Which Designed:</b>	0.250 Inches Nominal
<b>Material:</b>	Steel, Corrosion Resisting
<b>Material:</b>	Steel Corrosion Resisting
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Sleeve
<b>Surface Treatment:</b>	Passivated, Qq-p-35, Type 2
<b>Specification/standard Data:</b>	96906-ms51533 Government Standard And 81343-j514 Professional/industrial Association Standard
<b>Nondefinitive Spec/std Data:</b>	14 Figure

## How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-4K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.