

Description

Length: 13/32", stainless steel, passivate surface, MS20819 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208194K
Minimum Qty (MOQ):	5
NSN:	4730-00-629-0868
Schedule B:	7307.22.1000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS20819-4K Specifications

Casehardening Indicator:	Casehardened
Overall Length:	0.410 Inches Nominal
Metallic Hardness Rating:	70.0 Minimum Rockwell B And 95.0 Maximum Rockwell B
Flange Width:	0.140 Inches Nominal
Flange Outside Diameter:	0.383 Inches Nominal
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	0.328 Inches Nominal
Hose/tube Outside Diameter For Which Designed:	0.250 Inches Nominal
Material:	Steel, Corrosion Resisting
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Style Designator:	Sleeve
Surface Treatment:	Passivated, Qq-p-35, Type 2
Specification/standard Data:	96906-ms51533 Government Standard And 81343-j514 Professional/Industrial Association Standard
Nondefinitive Spec/std Data:	14 Figure

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-4K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.