

Description

tube outer diameter: 5/16", flared tube fitting, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------|
| SKU / Model: | MS208195D |
| Minimum Qty (MOQ): | 20 |
| NSN: | 4730-00-287-3053 |
| ECCN: | EAR99 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |



P/N MS20819-5D Specifications

| | |
|---|---|
| Casehardening Indicator: | Not Casehardened |
| Overall Length: | 0.438 Inches Nominal |
| Flange Width: | 0.156 Inches Nominal |
| Flange Outside Diameter: | 0.445 Inches Nominal |
| Seat Angle In Deg: | 33.0 |
| Sleeve Outside Diameter: | 0.366 Inches Nominal |
| Hose/tube Outside Diameter For Which Designed: | 0.313 Inches Nominal |
| Material: | Aluminum Alloy, Qq-a-225/9, Alloy 7075, T73 |
| Material: | Aluminum Alloy 7075 |
| Surface Treatment: | Anodize |
| Style Designator: | Sleeve |
| Surface Treatment: | Anodized, Mil-a-8625, Type 2 |

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.