

Description

outer diameter: 3/8", flared tube, corrosion resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AS5176J06](#)

SKU / Model:	MS208196J
Minimum Qty (MOQ):	10
NSN:	4730-00-595-3102
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



P/N MS20819-6J Specifications

Casehardening Indicator:	Not Casehardened
Overall Length:	0.500 Inches Nominal
End Item Identification:	Communications Satellite Terminal Model An/tsc-54, Boeing Vertol Cargo Transport Hel, Model Ch-47, Utility, Tactical Transport Uh-1 And Eh-1 (bell), Land Vehicle Lvt-7, Prs Mgm-31, F161 F18 Aircraft
Flange Width:	0.172 Inches Nominal
Flange Outside Diameter:	0.502 Inches Nominal
Seat Angle In Deg:	33.0
Sleeve Outside Diameter:	0.432 Inches Nominal
Hose/tube Outside Diameter For Which Designed:	0.375 Inches Nominal
Material:	Steel, Qq-s-763, Class 304
Material:	Steel Comp 304
Surface Treatment:	Passivate
Style Designator:	Sleeve
Surface Treatment:	Passivated
Specification/standard Data:	81349-mil-f-5509 Government Specification

How to Order

Order this flared tube fitting sleeve from our inventory online by visiting <https://military-fasteners.com/fittings/flared+tube+fitting+sleeves/MS20819-6j> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.