

Description

outer diameter: 1", tube thread: 1-5/16-12, pipe thread: 1", 37 degree angle, flared pipe to tube, aluminum alloy, MS20822 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2082216D
Minimum Qty (MOQ):	1
NSN:	4730-00-287-1025
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20822-16D Specifications

Nominal Pipe Size Accommodated:	1.000 Inches 2nd End
Thread Class:	3a 1st End
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	1.812 Inches Minimum 1st End And 1.859 Inches Maximum 1st End
Leg Length:	1.969 Inches Minimum 2nd End And 2.016 Inches Maximum 2nd End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Thread Quantity Per Inch:	12 1st End
Nominal Thread Size:	1.312 Inches 1st End
Nominal Thread Size:	1.000 Inches 2nd End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	1.000 Inches 1st End
Special Features:	Grumman A-10 Aircraft
Material:	Aluminum Alloy 2014 Overall
Material Document And Classification:	Qq-a-225/4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Inside
Surface Treatment:	Anodize Outside
Thread Series Designator:	Anpt 2nd End
Thread Series Designator:	Un 1st End
Specification/standard Data:	96906-ms20822 Government Standard And 88044-an822 Government Standard

How to Order

Order this pipe to tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-16D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.