

Description

tube outer dia: 3/16", tube thread: 3/8-24, pipe thread: 1/8", flared pipe to tube, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------|
| SKU / Model: | MS208223D |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-278-3680 |
| ECCN: | EAR99 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |

NO IMAGE
AVAILABLE

P/N MS20822-3D Specifications

| | |
|---|---|
| Nominal Pipe Size Accommodated: | 0.125 Inches 2nd End |
| Thread Class: | 3a 1st End |
| Connection Style: | Flared (tube) 1st End |
| Connection Style: | Plain (pipe) 2nd End |
| Leg Length: | 0.719 Inches Minimum 2nd End And 0.766 Inches Maximum 2nd End |
| Leg Length: | 0.828 Inches Minimum 1st End And 0.875 Inches Maximum 1st End |
| Connection Type: | Threaded External Pipe 2nd End |
| Connection Type: | Threaded External Tube 1st End |
| Thread Quantity Per Inch: | 27 2nd End |
| Nominal Thread Size: | 0.125 Inches 2nd End |
| Nominal Thread Size: | 0.375 Inches 1st End |
| Seat Angle: | 37.0 Degrees 1st End |
| Flow Angle: | 90.0 Degrees |
| Nominal Outside Diameter Tube Accommodated: | 0.188 Inches 1st End |
| Material: | Aluminum Alloy Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Anpt 2nd End |
| Thread Series Designator: | Unf 1st End |
| Specification/standard Data: | 96906-ms20822 Government Standard |

How to Order

Order this pipe to tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-3D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.