



★ FASTENERS

Military-Fasteners.com

P/N MS20822-3J

Description

tube outer diameter: 3/16", tube thread: 3/8-24, pipe thread: 1/8", 37 degree, flared pipe, corrosion resistant steel, MS20822 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208223J
Minimum Qty (MOQ):	1
NSN:	4730-00-402-0472
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N MS20822-3J Specifications

Nominal Pipe Size Accommodated:	0.125 Inches 2nd End
Thread Class:	3a 1st End
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	0.766 Inches Maximum 2nd End
Leg Length:	0.875 Inches Maximum 1st End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Thread Quantity Per Inch:	27 2nd End
Nominal Thread Size:	0.125 Inches 2nd End
Nominal Thread Size:	0.375 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.188 Inches 1st End
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072,e300,ty2 Mil Spec Single Treatment Response Outside
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Inside
Thread Series Designator:	Anpt 2nd End
Thread Series Designator:	Unf 1st End

How to Order

Order this pipe to tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-3J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.