

P/N MS20822-4

Description

tube outer dia: 1/4", tube thread: 7/16-20, pipe thread: 1/8", flared pipe to tube, carbon steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS208224

Minimum Qty (MOQ):

NSN: 4730-00-231-4009

ECCN: EAR99

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti







^{*} See page 2 for technical characteristics

P/N MS20822-4 Specifications

Thread Class:	3a 1st End
Maximum Operating Temp:	400.0 Deg Fahrenheit Single Response
End Item Identification:	Grumman A-10 Acft;2320-01-097-0248,2320-01-097-0249,2320-01-100-7672,2320-01-097-0260,2320-01-195-7641 Hemtt (heavy Expanded Mobility Tactical Trucks)
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	0.780 Inches Nominal 2nd End
Leg Length:	0.890 Inches Nominal 1st End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.125 Inches 2nd End
Nominal Thread Size:	0.438 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.250 Inches 1st End
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Anpt 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	96906-ms20822 Government Standard

How to Order

Order this pipe to tube elbow from our inventory online by visiting https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.