

P/N MS20822-5D

Description

tube outer dia: 5/16", tube thread: 1/2-20, pipe thread: 1/8", flared pipe to tube, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208225D
Minimum Qty (MOQ):	1
NSN:	4730-00-278-3678
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



^{*} See page 2 for technical characteristics

P/N MS20822-5D Specifications

Nominal Pipe Size Accommodated:	0.125 Inches 2nd End
Thread Class:	3a 1st End
End Item Identification:	Aircraft, F-16
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	0.781 Inches Minimum 2nd End And 0.828 Inches Maximum 2nd End
Leg Length:	0.953 Inches Minimum 1st End And 1.000 Inches Maximum 1st End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Thread Quantity Per Inch:	27 2nd End
Nominal Thread Size:	0.125 Inches 2nd End
Nominal Thread Size:	0.500 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Criticality Code Justification:	Feat
Nominal Outside Diameter Tube Accommodated:	0.312 Inches 1st End
Special Features:	Used On Grumman A10 Aircraft;weapon System Essential
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Inside
Surface Treatment:	Anodize Outside
Thread Series Designator:	Anpt 2nd End
Thread Series Designator:	Unf 1st End

How to Order

Order this pipe to tube elbow from our inventory online by visiting https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-5D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.