

## P/N MS20822-6-2

## **Description**

tube outer dia: 3/8", tube thread: 9/16-18, pipe thread: 1/8", 37°, flared pipe to tube, carbon steel

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2082262

Minimum Qty (MOQ):

NSN: 4730-00-618-9034

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20822-6-2 Specifications

Nominal Pipe Size Accommodated:	0.125 Inches 2nd End
Thread Class:	3a 1st End
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	1.031 Inches Minimum 1st End And 1.078 Inches Maximum 1st End
Leg Length:	0.875 Inches Minimum 2nd End And 0.922 Inches Maximum 2nd End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Nominal Thread Size:	0.125 Inches 2nd End
Nominal Thread Size:	0.562 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 1st End
Material:	Steel Overall
Surface Treatment:	Cadmium Inside And Chromate Inside
Surface Treatment:	Cadmium Outside And Chromate Outside
Thread Series Designator:	Anpt 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	96906-ms20822 Government Standard

## **How to Order**

Order this pipe to tube elbow from our inventory online by visiting <a href="https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-6-2">https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-6-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.