

Description

tube outer diameter: 3/8", tube thread: 9/16-18, pipe thread: 1/4", flared pipe to tube, aluminum alloy, MS20822 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS208226D
Minimum Qty (MOQ):	2
NSN:	4730-00-186-9968
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



* See page 2 for technical characteristics

P/N MS20822-6D Specifications

Thread Class:	3a 1st End
End Item Identification:	Aircraft Application;aircraft, F-16 (fighting Falcon)
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	1.062 Inches Nominal 1st End
Leg Length:	1.094 Inches Nominal 2nd End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Nominal Thread Size:	0.250 Inches 2nd End
Nominal Thread Size:	0.562 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Criticality Code Justification:	Feat
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 1st End
Special Features:	Grumman Aerospace A-10 Aircraft;weapon System Essential
Material:	Aluminum Alloy 2024 Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Anpt 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	81343-as5195 Government Standard

How to Order

Order this pipe to tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-6D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.