

## Description

tube outer dia: 3/8", tube thread: 9/16-18, pipe thread: 1/4", 37degree, flared pipe to tube, corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS208226J                                   |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 4730-00-639-9011                            |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



\* See page 2 for technical characteristics

## P/N MS20822-6J Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a 1st End  |
| <b>Connection Style:</b>                              | Flared (tube) 1st End                                     |
| <b>Connection Style:</b>                              | Plain (pipe) 2nd End                                      |
| <b>Leg Length:</b>                                    | 1.109 Inches Maximum 1st End                              |
| <b>Leg Length:</b>                                    | 1.141 Inches Nominal 2nd End                              |
| <b>Connection Type:</b>                               | Threaded External Pipe 2nd End                            |
| <b>Connection Type:</b>                               | Threaded External Tube 1st End                            |
| <b>Maximum Operating Pressure:</b>                    | 3000.0 Pounds Per Square Inch Single Response             |
| <b>Nominal Thread Size:</b>                           | 0.250 Inches 2nd End                                      |
| <b>Nominal Thread Size:</b>                           | 0.562 Inches 1st End                                      |
| <b>Seat Angle:</b>                                    | 37.0 Degrees 1st End                                      |
| <b>Flow Angle:</b>                                    | 90.0 Degrees  |
| <b>Nominal Outside Diameter Tube Accommodated:</b>    | 0.375 Inches 1st End                                      |
| <b>Material:</b>                                      | Steel Comp 347 Overall                                    |
| <b>Material Document And Classification:</b>          | Qq-s-763 Fed Spec Single Material Response Overall        |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35,type 1 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Anpt 2nd End  |
| <b>Thread Series Designator:</b>                      | Unjf 1st End  |
| <b>Specification/standard Data:</b>                   | 96906-ms20822 Government Standard                         |

## How to Order

Order this 90degree, elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-6J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.