

**Description**

tube outer dia: 3/8", tube thread: 9/16-18, pipe thread: 1/4", 37degree, flared pipe to tube, corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS208226J
Minimum Qty (MOQ):	1
NSN:	4730-00-639-9011
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE  
AVAILABLE

## P/N MS20822-6J Specifications

<b>Thread Class:</b>	3a 1st End
<b>Connection Style:</b>	Flared (tube) 1st End
<b>Connection Style:</b>	Plain (pipe) 2nd End
<b>Leg Length:</b>	1.109 Inches Maximum 1st End
<b>Leg Length:</b>	1.141 Inches Nominal 2nd End
<b>Connection Type:</b>	Threaded External Pipe 2nd End
<b>Connection Type:</b>	Threaded External Tube 1st End
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.250 Inches 2nd End
<b>Nominal Thread Size:</b>	0.562 Inches 1st End
<b>Seat Angle:</b>	37.0 Degrees 1st End
<b>Flow Angle:</b>	90.0 Degrees
<b>Nominal Outside Diameter Tube Accommodated:</b>	0.375 Inches 1st End
<b>Material:</b>	Steel Comp 347 Overall
<b>Material Document And Classification:</b>	Qq-s-763 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35,type 1 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Anpt 2nd End
<b>Thread Series Designator:</b>	Unjf 1st End
<b>Specification/standard Data:</b>	96906-ms20822 Government Standard

## How to Order

Order this 90degree, elbow from our inventory online by visiting <https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-6j> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.