

P/N MS20822-8

Description

tube outer diameter: 1/2", tube thread: 3/4-16, pipe thread: 3/8", flared pipe to tube, carbon steel

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS208228

Minimum Qty (MOQ):

NSN: 4730-00-231-3013

ECCN: EAR99

National Motor Freight: 052190, Pipe, tubing, or Pipe Or Tubing Fitti





^{*} See page 2 for technical characteristics

P/N MS20822-8 Specifications

Nominal Pipe Size Accommodated:	0.375 Inches 2nd End
Thread Class:	3a 1st End
Maximum Operating Temp:	-65.0 Deg Fahrenheit 1st Response
Maximum Operating Temp:	275.0 Deg Fahrenheit 2nd Response
Connection Style:	Flared (tube) 1st End
Connection Style:	Plain (pipe) 2nd End
Leg Length:	1.219 Inches Nominal 2nd End
Leg Length:	1.250 Inches Nominal 1st End
Connection Type:	Threaded External Pipe 2nd End
Connection Type:	Threaded External Tube 1st End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.375 Inches 2nd End
Nominal Thread Size:	0.750 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Nominal Outside Diameter Tube Accommodated:	0.500 Inches 1st End
Special Features:	Grumman Aerospace A-10 Aircraft
Material:	Steel Comp 1025 Overall
Material Document And Classification:	Mil-t-5066 Mil Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Npt 2nd End
Thread Series Designator:	Unf 1st End

How to Order

Order this pipe to tube elbow from our inventory online by visiting https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/fittings/pipe+to+tube+elbows/MS20822-8 and selecting the